


Technical data sheet for:

EBM 32, 40 und 50



General data

Item	Splitable connector - EBM 32, EBM 40, EBM 50
Description	Splitable connectors are used for the gas-and watertight sealing of connections between split duct (KKHR) and PE-duct.
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVenylChlorid - Unplastinized PVC-U	
Dimension	EBM 32: d = 32; L = 125;	mm
	EBM 40: d = 40; L = 125;	
	EBM 50: d = 50; L = 125;	
Pressure	0,5 (permanent gas- and watertight)	bar
	10 / 30	bar / min
Tensile strength	EBM 32: min. 1300	N
	EBM 40: min. 1300	
	EBM 50: min. 1500	
Pressing operation clamp on case	min. 1550	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: PW
 Release: MK
 Edition: 14.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.