


Technical data sheet for:

## EBM 32, 40 und 50



### General data

|                     |  |
|---------------------|--|
| <b>Item</b>         | Splitable connector - EBM 32, EBM 40, EBM 50   |
| <b>Description</b>  | Splitable connectors are used for the gas-and watertight sealing of connections between split duct (KKHR) and PE-duct. |
| <b>Package unit</b> | 12 Pcs.  |

### Technical data

| Quality                                 | Value                                  | Unit      |
|---|--|-----------|
| <b>Material</b>                         | PolyVenylChlorid - Unplastinized PVC-U |           |
| <b>Dimension</b>                        | EBM 32: d = 32; L = 125;               | mm        |
|   | EBM 40: d = 40; L = 125;               |           |
|   | EBM 50: d = 50; L = 125;               |           |
| <b>Pressure</b>                         | 0,5 (permanent gas- and watertight)    | bar       |
|   | 10 / 30                                | bar / min |
| <b>Tensile strength</b>                 | EBM 32: min. 1300                      | N         |
|   | EBM 40: min. 1300                      |           |
|   | EBM 50: min. 1500                      |           |
| <b>Pressing operation clamp on case</b> | min. 1550                              | N         |

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
 Am Schaidweg 7  
 94559 Niederwinkling  
 Germany

Phone 0049 (0)9962 950 200  
 Fax 0049 (0)9962 950 202  
 info@gabocom.de  
 www.gabocom.de

Editor: PW  
 Release: MK  
 Edition: 14.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.  
 Liability for damages is excluded.