CK6000-000 | IFDB-S-U-NN-1



IFDB Fiber Optic Wall Box with Universal splice holder for up to 4 mechanical or SMOUV splices

- Allows splicing those fibers from an indoor riser cable to the individual drops
- Allows fibers from certain riser cables to be broken out without interrupting the strength member
- Separate storage of un-connected fibers from spliced drop fibers
- Compatible with mechanical, SMOUV and ANT splice protectors
- In-line and butt configuration possible for main riser cable

Product Classification

Regional Availability EMEA

Product Type Fiber wall box

Product Series IFDB

General Specifications

Functionality Splicing

Adapters, quantity 0

ColorLight grayFront Cover TypeScrew-on

Mounting Floor | Wall

Splice Tray Chip Type Mechanical | SMOUV

Splicing Capacity, maximum 4

Dimensions

 Height
 80 mm | 3.15 in

 Width
 80 mm | 3.15 in

 Depth
 35 mm | 1.378 in

Material Specifications

Material Type Thermoplastic

Optical Specifications

Fiber Mode Singlemode



CK6000-000 | IFDB-S-U-NN-1

Environmental Specifications

Environmental Space Indoor

Flammability Rating UL 94 V-0

Qualification Standards IEC 60529, IP30

Packaging and Weights

Packaging quantity 20

Packaging Type Bag | Carton

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

