760238014 | SCIL-A-S24



SCIL-A Fiber splice closure, in-line, with 4 gel cable sealing kits, 1 pre-installed 24-splice tray and SMOUV protectors, no ground feedtrough lug, no air valve

- Leverages proven FOSC™ fiber management system, with multiple splice tray options
- Removeable cover allows unrestricted access to cable termination and splice area for easier installation
- Cable termination and retention system fits any cable type from traditional loose tube buffered to small micro-sheath cables

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin

America | North America

Product Type In-line, rectangular fiber closure

Product Brand SCIL™

Product Series SCIL-A

General Specifications

Cable Entry Drop Port StyleRoundCable Entry Main Port StyleRoundCable Ports, quantity10

Cable Sealing Type Compressed gel

Closure Sealing Type Side latch
Closure Style In-line
Color Black

Mounting Facade | Wall

Network Area Type Drop

Splice Tray Included, quantity

Splice Tray Type Included 24-way, heat shrink

Splicing Capacity, Single Fusion, maximum 48
Splicing Capacity, Single Splice, 12 fibers, maximum 48

Splicing Type, Supported Single fusion

Dimensions

COMMSC PE°

760238014 | SCIL-A-S24

 Height
 70 mm | 2.756 in

 Width
 100 mm | 3.937 in

 Length
 200 mm | 7.874 in

 Main Cable Diameter, maximum
 11 mm | 0.433 in

Ordering Tree

S C I L - A - ___



Material Specifications

Material Type Rugged polymer

Environmental Specifications

Environmental SpaceAbove ground| Below groundQualification StandardsIEC 60529, IP68 + 2 m waterhead

Packaging and Weights

Included SMOUV splice protectors (24)

Packaging quantity 1

Packaging TypeBox| CartonWeight, net1 kg| 2.205 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



760238014 | SCIL-A-S24





Page 3 of 3

