

Coaxial Adapter N female - female FEATURES / BENEFITS



Technical features

STRUCTURE		
Product Line	Coaxial Cable Components	
Product Type	Coaxial Adapter	
MECHANICAL CRECIFICATIONS		

MECHANICAL SPECIFICATIONS

Connector A	N Female
Center Contact Connector A	Phosphor Bronze, silver plated
Outer Contact Connector A	Brass, Tri metal alloy plated
Connector B	N Female
Center Contact Connector B	Phosphor Bronze, silver plated
Outer Contact Connector B	Brass,Tri metal alloy plated
Dielectric	PTFE
Sealing class	IP68, connected

ELECTRICAL SPECIFICATIONS

Frequency Range - MHz		DC - 6000		
VSWR, Return Loss	0-2000 MHz: 1.04 (34.15) VSWR (dB) 2000-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44)			
Insertion Loss, dB (Max)	dB	0.05		
3rd Order IM Product @ 2x20 Watts	dBc	< -163		

TEMPERATURE SPECIFICATIONS

Operation Temperature °C (°F)		-45 to 85 (-49 to 185)	

PACKAGING INFORMATION

Package Quantity	1	

External Document Links

Notes

NF-NF REV : E REV DATE : N/A www.rfsworld.com