


UFXLULU62



Ultra Low Loss OM4, LC Uniboot to LC Uniboot, 2.0 mm Duplex Fiber Patch Cord, Low Smoke Zero Halogen/Riser

- Patch cords using Uniboot technology combine, modularity, flexibility with easy insertion and removal from connectivity
- Uniboot connectors feature an adjustable polarity via a manual and independent rotation of each single connector body without exposing the fibers
- Uniboot technology features a push-pull mechanism operated by squeezing the connector boot

Product Classification

| | |
|------------------------------|--|
| Regional Availability | Asia Australia/New Zealand Europe Latin America Middle East /Africa North America |
| Portfolio | CommScope® |
| Product Type | Fiber patch cord, duplex |
| Product Brand | SYSTIMAX ULL |
| Ordering Note | For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration |

General Specifications


| | |
|---------------------------------------|---------|
| Color, connector A | Beige |
| Color, connector B | Beige |
| Interface, Connector A | LC/UPC |
| Interface Feature, connector A | Uniboot |
| Interface, Connector B | LC/UPC |
| Interface Feature, connector B | Uniboot |
| Jacket Color | Aqua |
| Total Fibers, quantity | 2 |

Dimensions

| | |
|--|-----------------|
| Cable Assembly Length, minimum (ft) | 2 |
| Cable Assembly Length, maximum (ft) | 200 |
| Cable Assembly Length, minimum (m) | 1 |
| Cable Assembly Length, maximum (m) | 61 |
| Diameter Over Jacket | 2 mm 0.079 in |

UFXLULU62

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum 11.24 lb @ 0 ° | 4.40 lb @ 90 °

Optical Specifications

Fiber Mode Multimode
Fiber Type OM4, LazrSPEED®
Insertion Loss, maximum 0.15 dB
Return Loss, minimum 35 dB

Environmental Specifications

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space Dual Rated LSZH/Riser

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Above maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant/Exempted |



Included Products

760152074 N-002-MP-5K-F20AQ – LazrSPEED® Low Smoke Zero Halogen Riser Light Duty Interconnect Cable, 2 fiber
860650410

UFXLULU62

COMMSCOPE

- LazrSPEED® LC UniBoot 2.0MM MM/LC UNIBOOT CONNECTOR KIT