


Coaxial Adapter, 4.3-10 Male/Female Right Angle FEATURES / BENEFITS



Technical features

STRUCTURE				
Product Line			Coaxial Cable Components	
Product Type			Coaxial Adapter	
MECHANICAL SPECIFICATIONS				
Connector A			4.3-10 Male	
Center Contact Connector A			Brass, silver plated	
Outer Contact Connector A			Brass, Tri metal plated	
Connector B			4.3-10 Female	
Center Contact Connector B			Brass, silver plated	
Outer Contact Connector B			Brass, Tri metal plated	
Dielectric			PTFE	
Gasket			Silicone rubber	
Sealing class			IP68, connected	
ELECTRICAL SPECIFICATIONS				
Frequency Range - MHz			DC - 6000	
VSWR, Return Loss	VSWR (dB)		0 TO 2 GHz VSWR 1.05 (32.25) 2 TO 3 GHz VSWR 1.08 (28.3) 3 TO 6 GHz VSWR 1.12 (24.94)	
Insertion Loss, dB (Max)	dB		0.05	
3rd Order IM Product @ 2x20 Watts	dBc		-163	
TEMPERATURE SPECIFICATIONS				
Operation Temperature	°C (°F)		-40 to 85 (-40 to 185)	
PACKAGING INFORMATION				
Package Quantity			1	
External Document Links			Notes	
I3M-R-43F	REV : B		REV DATE : N/A	www.rfsworld.co