



G2 MPOptimate® Singlemode MPO-12 Distribution Module, 12LC to 1x12f MPO pinned , internal shutters

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Fiber module
<b>Product Series</b>	G2

## General Specifications

<b>Color, front</b>	Blue
<b>Color, rear</b>	Black
<b>Interface, front</b>	LC
<b>Interface Feature, front</b>	UPC
<b>Interface, rear</b>	MPO Pinned
<b>Interface Feature, rear</b>	Key up/down
<b>Polarity</b>	Method A   Pairs, straight
<b>Shuttered</b>	Yes
<b>Total Fibers, quantity</b>	12

## Dimensions

<b>Height</b>	26.42 mm   1.04 in
<b>Width</b>	96.52 mm   3.8 in
<b>Depth</b>	117.35 mm   4.62 in

## Optical Specifications

<b>Fiber Mode</b>	Singlemode
<b>Fiber Type</b>	OS2

# 760242498 | DM12-12LC-SM-A

Insertion Loss, maximum 0.6 dB

## Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL

## Packaging and Weights

Packaging quantity 1

Weight, net 0.01 kg | 0.022 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant/Exempted

