

# MPO Patch Cords

## Product Overview

MPO Patch Cords use a compact and rugged 3mm cable that optimizes space in patching areas and contributes to improved airflow. MPO Patch Cords facilitate rapid deployment of high-density cabling in data centers or other high fiber density environments, reducing network installation or reconfiguration time and cost. Utilize these assemblies for quick and easy patching between data center zones or to interconnect MPO active equipment ports.

## Features

### Fiber and Cable Options

- Available in SM (OS1/2 G.657A1/A2), OM3, OM4
- Compact LSZH, OFNR, OFNP cable jackets available
- Jacket Standard Colours: SM Yellow, OM3 Aqua, OM4 Aqua (OM4 Erika Violet Available)

### MPO Interface

- Female and Male MPO connectors available
- Base-8, Base-12 available (for Base-16, and Base-24 contact sales rep)
- Standards based polarity options available

### Optimized Performance

- Low loss Premium MPO connectors and Bend Insensitive fiber assure low insertion losses and reduced power penalties in tight budget high-speed network environments
- 100% factory tested for proven reliability connectivity
- Manufactured in accordance with TIA 568 and IEC 61754 standards



## Benefits

### Next Generation Network Speeds

- Assemblies can be used throughout multiple active equipment upgrades in order to future-proof your network
- Modular connectivity support 400G/800G migration plans

### Rapid Deployment

- Factory terminated assembly saves installation and reconfiguration time during moves, adds and changes
- Configurable length assemblies reduce slack management, patch field congestion, and improved air-flow



## Applications

- Data Center
- Campus
- Central Office
- Office Backbone

## Specifications

Connector Mating	Insertion Loss Max	Return Loss
Multimode Premium	0.35 dB	≤ -25 dB
Single-Mode Premium	0.35 dB	≤ -60 dB

## Cable Specifications

Fiber count	Cable diameter (mm)	Crush resistance	Cable tensile strength (installed)	Bend Radius Installed	Storage temperature	Installation Temperature	Operating Temperature	Fibers
8	2.9 ±0.1	500N/100mm	200N	30mm	-20 ~ +70°C	0 ~ 60°C	0 ~ 60°C	OM4, SM G657A1
12	2.9 ±0.1	500N/100mm	200N	30mm				

## Cable performance

Cabled Fibre Type (ISO/IEC 11801)	SM (OS1/OS2)	OM3	OM4
Attenuation Coefficient [dB/km]	≤0.38 Max (1310 nm) ≤0.25 Max (1550 nm) ≤0.34 Typ (1310 nm) ≤0.19 Typ (1550nm)	≤ 3.5 Max (850 nm) ≤ 1.5 Max (1300 nm) ≤ 2.7 Typ (850 nm) ≤ 0.9 Typ (1300 nm)	≤ 3.5 Max (850 nm) ≤ 1.5 Max (1300 nm) ≤ 2.7 Typ (850 nm) ≤ 0.9 Typ (1300 nm)
Minimum Bandwidth: Overfilled Launch [Mhz-km]	N/A	≥ 1500 (850 nm) ≥ 500 (1300 nm)	≥ 3500 (850 nm) ≥ 500 (1300 nm)
Minimum Bandwidth: Laser Effective Modal Bandwidth [Mhz-km]	N/A	≥ 2000 (850 nm)	≥ 4700 (850 nm)



### Ordering Information

	Description	Part Number
Base-8	12 Fiber, OM4, Premium MPO (F) to MPO (F) Base-8 Trunk, Indoor MicroCable 3mm (Aqua), Pol B, CPR Cca, Xm	M4DQBCCPUU-B002-MX
	12 Fiber, SM, Premium MPO (Female) to MPO (Female) Base-8 Trunk, Indoor MicroCable 3mm (Yellow), Pol B, CPR Cca, Xm	M7DQBCC9PUU-B002-MX
Base-12	12 Fiber, OM4, Premium MPO (F) to MPO (F) Base-12 Trunk, Indoor MicroCable (Aqua), Pol B, CPR Cca, Xm	M4DQBCCPUU-B028-MX
	12 Fiber, SM Premium MPO (F) to MPO (F) Base-12 Trunk, Indoor MicroCable (Yellow), Pol B, CPR Cca, Xm	M7DQBCC9PUU-B028-MX

### Part Number Generator

Code	Fiber Type	Fiber Count	Jacket Material	Color	Code	End A	End B	Polarity	Unit	Length
M	3 OM3	DQB	L LSZH	9 Yellow	P	U MPOF	U MPOF	-A028 Polarity A	M Meters	1 1
	4 OM4		E CPR Eca	C Aqua		V MPOM	V MPOM	-B028 Polarity B	F Feet	2 1
	7 G.657A1		C CPR Cca	D Erika Violet			X Open	-C028 Polarity C		3 3
	8 G.657A2		B CPR B2ca							5 5
			R OFNR							10 10
			Q OFNR UL Listed							x Specify
			P OFNP							
			A OFNP UL Listed							

### Regional Availability

#### USA

+1-866-814-8615  
usasales-hyp@aflglobal.com

#### EMEA

+44 1908 441 144  
emeasales-hyp@aflglobal.com

#### INDIA

+91 80 46874687  
indiasales-hyp@aflglobal.com

#### APAC

(excluding India)  
+86 755 2561 3694  
apacsales-hyp@aflglobal.com

