

Netscale 48 Cassette 6x LC-Duplex SM PC black

**DESCRIPTION**

Netscale splice cassette

Connect all your cable type with all fiber to all connector types.

Netscale splice cassette

Connect all your cable type like Loose-tube, micro-tube, minicore and ribbon cables with all fiber types like multi-mode OM4, OM5 or single-mode G.657.D and G.657.A to and connector types like MPO, LC, SC, E2000TM.

021.5940 / similar product

SCOPE OF SUPPLY

1 x Netscale 48 FO Cassette
6 x LC duplex adapter SM PC

TENDER

Netscale 48 adapter cassette, 6 x LC duplex adapter singlemode PC according to IEC 61754-20 blue,

Housing: Polycarbonate fire class UL 94V-0, black RAL 9005

Dimensions: 103 x 108 x 18 mm (L x W x H)

Manufacturer: R&M

Type: 1 x R 869113

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Capacity (ports)	6
Standard	Protection class: IP20 acc. to IEC 60529


MECHANICAL DATA




DESCRIPTION	VALUE / VALUE RANGE
Dimensions	108.0 mm x 18.8 mm x 103.0 mm / 4.252 in x 0.74 in x 4.055 in (W x H x D)
Color Code RAL	9005 Jet black
Material	PC + ABS halogen-free, UL 94 V-0

ENVIRONMENTAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Operation temperature	-10 °C to +60 °C / +14 °F to +140 °F

ACCESSORIES

Type	Picture	Description	Article	E-Number
Accessories		Netscale 48 empty 1U straight	R868288	966733105

Type	Picture	Description	Article	E-Number
Accessories		Netscale 48 empty 1U angled	R875195	
Accessories		Netscale 48 empty 1U straight with Front	R875196	966733115
Accessories		Netscale 48 empty 1U straight with Front	R875197	966733125