

Netscale 48 Cassette 6 Port MPO Type A black

**DESCRIPTION**

Netscale splice cassette

Connect all your cable type with all fiber to all connector types.

Netscale splice cassette

Connect all your cable type like Loose-tube, micro-tube, minicore and ribbon cables with all fiber types like multi-mode OM4, OM5 or single-mode G.657.D and G.657.A to and connector types like MPO, LC, SC, E2000TM.

021.5942

SCOPE OF SUPPLY

1 x Netscale 48 FO Cassette

6 x MPO adapters

TENDER

Netscale 48 adapter cassette, 6 x MPO connector according to IEC 61754-7 black, Key Up/Key Down

Housing: Polycarbonate fire class UL 94V-0, black RAL 9005

Dimensions: 103 x 108 x 18 mm (L x W x H)

Manufacturer: R&M

Type: 1 x R868295

TECHNICAL DATA

| DESCRIPTION | VALUE / VALUE RANGE |
|------------------|--|
| Capacity (ports) | 6 |
| Standard | Protection class: IP20 acc. to IEC 60529 |


MECHANICAL DATA




| DESCRIPTION | VALUE / VALUE RANGE |
|----------------|---|
| Dimensions | 108.0 mm x 18.8 mm x 103.0 mm / 4.252 in x 0.74 in x 4.055 in (W x H x D) |
| Color Code RAL | 9005 Jet black |
| Material | PC + ABS halogen-free, UL 94 V-0 |

ENVIRONMENTAL DATA

| DESCRIPTION | VALUE / VALUE RANGE |
|-----------------------|--------------------------------------|
| Operation temperature | -10 °C to +60 °C / +14 °F to +140 °F |

ACCESSORIES

| Type | Picture | Description | Article | E-Number |
|-------------|---|-------------------------------|---------|-----------|
| Accessories |  | Netscale 48 empty 1U straight | R868288 | 966733105 |

| Type | Picture | Description | Article | E-Number |
|-------------|---|--|---------|-----------|
| Accessories |  | Netscale 48 empty 1U angled | R875195 | |
| Accessories |  | Netscale 48 empty 1U straight with Front | R875196 | 966733115 |
| Accessories |  | Netscale 48 empty 1U straight with Front | R875197 | 966733125 |