

1U-UniRack2-IR-0-f LSH/SC/LCDno-no

DESCRIPTION

Special mounting brackets for mounting the R&MinteliPhy Sensorbar.



090.7564 / similar product

TENDER

Splice and patch box, mounting depth 225 mm, continuously depth-adjustable up to 55 mm; rear cable feed, cable entry possible from three different angles. The box has two levels, the lower level serves as storage for spare loose tubes, tray fixation in the side structure is ensured; the upper level serves as storage for spare pigtails (1.3 m of fiber stored in the splice tray). Guaranteed bending radius ≥ 40 mm, fitted ready for splicing with pigtails and adapters, inserted and tested, two splice trays with radius 40 mm, box continuously extendable up to 210 mm, at full extension it can be inclined 10° forwards. Optimum access to loose tubes, adapters and pigtails, the tray can be fully detached from the box by release lever. Special mounting brackets for mounting the R&MinteliPhy Sensorbar. Includes indelible laser trademark, fastening material, labeling strips and installation instructions.

Features:

- Dimensions: 43.6 x 482.6 x 225 mm
- Material: box, powder-coated sheet steel / front panel, plastic PC, fiber-glass reinforced
- Color: medium gray (NCS 2502-B, approximating RAL 7035)

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Amount of height units	1 U
Rack mounting version	patch panel
Adapter fastening method	end cap snap-in
Assembly	empty
Capacity (ports)	24
Sleeve material	ceramic
Version	splice
Amount of height units	1 U
Standard	IEC 60297-3: 19-inch (482.6 mm) rack
Fastening	19 " U

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	43.6 mm x 482.6 mm x 225.0 mm / 1.717 in x 19 in x 8.858 in (W x H x D)
Color Code NCS	S 2502-B
Material	steel: DC01 (1.0330), 1.0 mm