

MPO Modul HD, 2xMTP12-female - 12xLC-Duplex, OM4, PC/PC, type A, gray



DESCRIPTION

PRODUCT_IMAGE

SCOPE OF SUPPLY

- Slide-in unit, radius limiter radius 30 mm, labeling strips and installation instructions
- Plastic front panel equipped with 12 x LC-Duplex adapters and fan-outs inserted, rear side two MTP12-female connectors mounted

TENDER

- MPO Modul HD front populated with 12 LC-Duplex adapters (split sleeve ceramic), at the back mounted with two MTP12-female adapters (type A), with 12-faser fan-outs, MM 50 µm OM4, assembly class in acc. with IEC 61753-1; the wiring inside the module is straight, key up to key down (according to method A from standard TIA 568-C); geometrical specifications of MPO (MTP) connectors in acc. with IEC 61754-7; incl. radius limiter at radius 30 mm and hold-down cross, fully populated, plastic front panel featuring per-numbered ports, tool-free locking and unlocking system and offering individual labeling options.

Features:

- Dimensions: 43.2 x 109.9 x 217 mm (W x H x D)
- Material: module and front panel: plastic (PC, fiber-glass reinforced, halogen-free, UL 94 V-0)
- Color: module and front panel: light gray (NCS 1005-R80B)

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Fiber type	Multimode (MM)
Conductor type FO	semi-tight buffer, dry
Fiber class	OM4
Fiber diameter	G50 / 125 µm
Number of connectors (A)	2
Number of connectors (B)	12
Connector type (A)	MPO, female
Connector type (B)	LC-Duplex
Connector color (A)	black
Connector color (B)	heather violet
Polishing plug (A)	PC
Polishing plug (B)	PC
Protection class IP (A)	IP 20
Protection class IP (B)	IP 20

Protection class IP	IP 20
Return loss (RL)	≥ 35 dB
Insertion loss (IL) max. value	≤ 0.35 dB
Attenuation grade IL (A)	Cm
Wiring diagram	type A
Rack mounting version	slide-in unit
Adapter fastening method	end cap snap-in
Assembly	fully populated
Sleeve material	ceramic
Standard	UL Listed

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	43.2 mm x 109.9 mm x 217.0 mm / 1.701 in x 4.327 in x 8.543 in (W x H x D)
Color Code NCS	S 1005-R80B
Material	plastic: PC, fiber-glass reinforced, halogen-free

ENVIRONMENTAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Operation temperature	10 °C to 60 °C / +50 °F to +140 °F